## COMPRESSOR DATA SHEET

Federal Uniform Test Method for Certain Air Compressors Not Applicable Rotary Compressor: Fixed Speed

MODEL DATA - FOR COMPRESSED AIR					
1	Manufacturer: ELGi				
	Model Number: OF275-145	Date:	07-11-2024		
2	Air-cooled X Water-cooled	Type:	SCREW		
	Oil-injected X Oil-free	# of Stages:	2		
3*	Rated Capacity at Full Load Operating Pressure a.c	1438	a,e acfm		
4	Full Load Operating Pressure <sup>b</sup>	145	psig <sup>b</sup>		
5	Maximum Full Flow Operating Pressure <sup>c</sup>	148	psig <sup>c</sup>		
6	Drive Motor Nominal Rating	400	hp		
7	Drive Motor Nominal Efficiency	95.8	percent		
8	Fan Motor Nominal Rating (if applicable)	NIL	hp		
9	Fan Motor Nominal Efficiency	NA	percent		
10*	Total Package Input Power at Zero Flow <sup>e</sup>	57.29	e kW		
11	Total Package Input Power at Rated Capacity and Full Load Operating Pressure <sup>d</sup>	286.45	$kW^d$		
12*	Specific Package Input Power at Rated Capacity and Full Load Operating Pressure <sup>e</sup>	19.92	kW/100 cfm <sup>e</sup>		

\*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator. Consult CAGI website for a list of participants in the third party verification program: www.cagi.org

NOTES: a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.

- b. The operating pressure at which the Capacity ( $\hat{\text{Item 3}}$ ) and Electrical Consumption ( $\hat{\text{Item 11}}$ ) were measured for this data sheet.
- c. Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the maximum pressure attainable before capacity control begins. May require additional power.
- d. Total package input power at other than reported operating points will vary with control strategy.
- e. Tolerance is specified in ISO 1217, Annex C, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.



Member

Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
m <sup>3</sup> / min	ft³ / min	%	%	%
Below 0.5	Below 17.6	+/- 7	+/- 8	
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	
1.5 to 15	53 to 529.7	+/- 5	+/- 6	+/- 10%
Above 15	Above 529.7	+/- 4	+/- 5	

ROT 030.2

2/19 Rev 3 This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported data.