F			Rotary Compressor: Fixed S			
_		- - -	MODEL DATA - FOR COMPRES	SED AIR		
	1	Manufacturer: ELGi				
	Model Number: EG 110-150-SP			Date:	11/29/2023	
	2	X Air-cooled Water-cooled		Type:	SCREW	
			# of Stages: 2			
	3*	Rated Capacity at Full Loa	d Operating Pressure ^{a, e}	595	acfm ^{a,e}	
	4*	Full Load Operating Press		150	psig ^b	
-	5		imum Full Flow Operating Pressure		psig ^c	
-	6	Drive Motor Nominal Rating		165 150		_
-		Drive Motor Nominal Effi		95.8 2.1 X 2	percent	_
-	7		5			_
-	8		Aotor Nominal Rating (if applicable) Aotor Nominal Efficiency		hp percent	_
-	9					_
-	10*	Total Package Input Power		29.51	kW ^e	_
	11	Operating Pressure ^d	tal Package Input Power at Rated Capacity and Full Load erating Pressure ^d		kW^d	
	12*	Package Specific Power at Rated Capacity and Full Load Operating Pressure ^e Isentropic Efficiency		114.81 19.30	kW/100 cfm ^e	
	12*					
	13			85.72	Percent	
Ľ	*For mod	els that are tested in the CAGI Pe	erformance Verification Program, these items are	verified by the third party	administrator.	
PAR ressed Air & Gas	NOTES	 a. Measured at the discha ISO 1217, Annex C; A b. The operating pressure for this data sheet. c. Maximum pressure attr maximum pressure attra d. Total package input po- e. Tolerance is specified 	pants in the third party verification program: rge terminal point of the compressor package in accor CFM is actual cubic feet per minute at inlet condition at which the Capacity (Item 3) and Electrical Consun ainable at full flow, usually the unload pressure setting inable before capacity control begins. May require ac wer at other than reported operating points will vary v in ISO 1217, Annex C, as shown in table below: wer" and "energy" are synonymous for purposes of th	s. nption (Item 11) were measu g for load/no load control or dditional power. with control strategy.		
		Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	Zero I Pow
Member		<u>m³/min</u>	$\frac{\text{ft}^3 / \text{min}}{1}$	%	%	%
		Below 0.5	Below 17.6	+/- 7	+/- 8	
		0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/-
		1.5 to 15 Above 15	53 to 529.7 Above 529.7	+/- 5 +/- 4	+/- 6 +/- 5	